



DX Electric – XPF, and XPF-FR

Description

DX Electric – XPF and XPF-FR are light weight, self-fitting, monofilament sleeveings designed to encapsulate and protect cable bundles and wire assemblies. These expandable sleeveings adjust to irregular surfaces and contours, providing abrasion resistance and protection with a minimum of bulk and weight. Polyester expandable sleeving is available in normal (XPF) and flame retardant (XPF-FR)

Standard

- Material: Polyethylene terephthalate (PET)
- Monofilament: .010
- UL File Number: E142828
- RoHS Compliant
- Operating Temp. Range: -94°F (-70°C) to 257°F (125°C)
- Melting Temp: 482°F/250°C
- Flammability: VW-1

Specification Values

Non-Flame Retardant Catalog Number Size	Flame Retardant Catalog Number Size	Nominal I.D.		Bundle Size Range (Minimum-Maximum)		Approximate Weight lbs/ft	Std. Length ft/spool
		Inches	mm	Inches	mm		
XPF-18B	XPF-18B-FR	0.125	3.18	0.094-0.125	2.38-3.18	0.17	100, 1000
XPF-14B	XPF-14B-FR	0.250	6.35	0.125-0.375	3.18-9.53	0.25	100, 1000
XPF-38B	XPF-38B-FR	0.375	9.53	0.250-0.625	6.35-15.88	0.6	100, 1000
XPF-12B	XPF-12B-FR	0.500	12.70	0.250-0.750	6.35-19.05	0.75	100, 500
XPF-58B	XPF-58B-FR	0.625	15.88	0.375-1.000	9.53-25.40	0.95	100, 500
XPF-34B	XPF-34B-FR	0.750	19.05	0.500-1.250	12.70-31.75	1.25	100, 250
XPF-114B	XPF-114B-FR	1.250	31.75	0.750-1.500	19.05-38.10	1.65	100, 250
XPF-112B	XPF-112B-FR	1.500	38.00	1.000-2.500	25.40-63.50	1.97	100, 250
XPF-134B	XPF-134B-FR	1.750	44.45	1.250-2.750	31.75-69.85	2.75	100, 200
XPF-2B	XPF-2B-FR	2.000	50.80	1.500-3.000	38.10-76.20	3.00	100
XPF-212B	XPF-212B-FR	2.500	63.50	1.750-3.500	44.45-89.90	4.65	100
XPF-3B	XPF-3B-FR	3.000	76.20	2.000-4.000	50.80-101.6	3.40	100
XPF-312B	XPF-312B-FR	3.500	88.90	2.500-5.500	63.50-139.7	4.00	100
XPF-4B	XPF-4B-FR	5.000	125	3.500-7.000	88.90-177.0	4.20	100

Standard Colors: Black. White available on special request

