



Spiral Wrap

Applications

Bundles wires, cables, hoses, and tubing firmly but allows flexibility. Functional and decorative, it wraps on like tape and can be reused quickly and simply. Spiral wrap permits breakouts in any orientation and is easy to route or reroute. It organizes, insulates, and resists abrasion.

Features

- Install gapped for greater flexibility or butted for maximum abrasion resistance, insulation, and rigidity
- Polyethylene
- Made in the U.S.A.

Properties

Max Operating Temperature	190°F (88°C)
Min Operating Temperature	-76°F (-60°C)
Tensile strength @ 73° (D-412-51T)	1800 psi
Specific Gravity (D792-66)	0.92
Effect of Solvents (at ambient)	None below 122°F (50°C)
Effect of Acids (at ambient)	None
Effect of Alkalies (at ambient)	None
Water Absorption % (D-570)	.014
Flammability	Flammable
UL File Number	E83405

Dimensions

Part Number	Size Inches	O.D. Inches	Wall Thickness Inches	Nominal I.D. Inches	Pitch Inches	Max Bundle Range Inches
SW-18	1/8	.125	.032	.061	.187	1/16 – 1/2
SW-14	1/4	.250	.045	.160	.375	3/16 – 2
SW-38	3/8	.375	.052	.271	.438	5/16 – 3
SW-12	1/2	.500	.062	.375	.563	3/8 – 4
SW-34	3/4	.750	.065	.620	.750	3/4 – 5
SW-1	1	1.00	.080	.840	1.00	1 – 7
SW-114	1-1/4	1.25	.090	1.07	1.25	1-1/4 – 8
SW-112	1-1/2	1.50	.100	1.30	1.50	1-1/2 – 10

Standard Color: Natural and Black